



NOTES:

- 1.) 3-RAIL PVC ROUTED EQUESTRIAN FENCING, AVAILABLE FROM:
 - ULTRA GUARD FENCE PRODUCTS, 3773 STATE ROAD, CUYAHOGA FALLS, OHIO 44223 PHONE (800) 457-1275, WEB: WWW.ULTRAGUARDVINYLFENCE.COM
 - OR APPROVED EQUAL

- 2.) PVC FENCE COLOR SHALL BE TAN, UNLESS INDICATED OTHERWISE
- 3.) POST SHALL BE INSTALLED ONTO EZ-55 BRACKETS AND STEEL POST, WHERE REQUIRED. SEE STD MVGF-613F-0 FOR EZ-55 BRACKET DETAIL.
- 4.) 2000 PSI MINIMUM STRENGTH CONCRETE SHALL BE POURED INTO POSTHOLE, THEN THE POST DRIVEN INTO THE CONCRETE.
- 5.) 'GREEN BOOK' STANDARDS SHALL BE IN AFFECT FOR ALL CONCRETE.
- 6.) POSTS SHALL BE INSTALLED PLUMB
- 7.) POST ROUTING: FIRST HOLE SHALL BE 3" FROM THE TOP OF POST. MID RAIL IS TO BE SPACED 11" FROM BOTTOM OF TOP RAIL TO TOP OF MID RAIL. THIRD RAIL IS TO BE SPACED 11" FROM BOTTOM OF MID RAIL TO TOP OF THIRD RAIL. THIRD RAIL IS TO HAVE APPROXIMATELY 11" SPACING FROM BOTTOM OF THIRD RAIL TO FINISH GRADE. FINISH GRADE SHALL BE CALCULATED TO DECOMPOSED GRANITE PATH.
- 8.) RAILS SHALL BE 2"x6"x16" PVC WITH RAIL LOCKS ON EACH SECTION. NOMINAL SIZES ARE NOT ACCEPTABLE.

NOT TO SCALE



RECOMMENDED: *[Signature]* 1/21/14
 DIVISION MANAGER DATE
 APPROVED: *[Signature]* 1/29/14
 PUBLIC WORKS DIRECTOR / DATE
 CITY ENGINEER

CITY OF MORENO VALLEY
 PARKS AND COMMUNITY SERVICES DEPARTMENT

3-RAIL PVC FENCE

STANDARD PLAN
MVGF-640-0
 SHEET 1 OF 1